



RxCheck

Prescription Monitoring Program

Information Exchange

RxCheck State Routing Service

SRS Installation & Setup Guide

for HCEs

Delivery On:	Dec 2025
Version:	3.2.1
Prepared By:	IJIS Institute Tetra Ventures
Sponsored By:	Bureau of Justice Assistance



Contents

Introduction.....	3
Overview.....	3
Specifications.....	3
PMIX Architecture.....	3
RxCheck / SRS Connection	4
Installation Procedure	5
Step 1: Download Package and Prepare the pre-installation checklist.....	5
Step 2: Network Preparation	5
Step 3: Security	7
Step 4: Install Application	8
Install RxCheck SRS Package	8
Configure RxCheck SRS	9
Step 5: Complete SRS Configuration on the RxCheck Console	10
Step 6: Starting RxCheck SRS	12
Step 7: Conduct Simulator Testing.....	14
Step 8: Integration Testing.....	14

Figures

Figure 1: PMIX Overview	3
Figure 2: Typical RxCheck Integration Architecture Overview.....	15

Introduction

Overview

The PMIX service provides state PMP systems with the capability to retrieve interstate prescription drug history and display it to their in-state end users (requestor) to assist in the identification of potential abuse and diversion. The service can provide the requested drug history as a direct response to a request containing person identifiers. Multiple concurrent requests can be issued by an HCE system to provide prescription drug histories from as many states as needed.

Specifications

PMIX Architecture

The Prescription Drug Monitoring Program Training and Technical Assistance Center (PDMP TTAC) and other stakeholders have undertaken the development of a consensus, national PMIX Architecture to enable the interstate sharing of PMP data. The use of open, consensus standards promotes interoperability. The National Information Exchange Model (NIEM) and the Global Reference Architecture (GRA) are foundational standards of the PMIX Architecture.

The PMIX architecture requires

1. Common NIEM exchange data and metadata,
2. Hub connections and
3. End-to-end security (including encryption key management).

The architecture will result in a shared infrastructure to support certificate/key management capabilities and essential directory services, specifically the PMIX Directory Service. The PMIX Directory, also known as the PMIX PKI Server, provided for X.509 certificate management and public key exchange as well as PMP contact and service requirement information.




Figure 1: PMIX Overview

RxCheck / SRS Connection

The PMIX service interface utilizes standards-based web services to facilitate communication through hubs to the endpoint systems. The following diagram shows an HCE system connecting to the PMIX RxCheck Hub via the PMIX State Routing Service (SRS). The PMIX SRS enables HCEs to “offload” PMIX functionality such as PMIX compliant service hosting, request/response message validation, role-based site authorization, full message routing and message translation.




Figure 2: PMIX RxCheck/SRS Architecture Detail

The web service interfaces are protected by a combination of Transport Layer Security (TLS), which provides transport-level encryption and service authentication and message-level encryption, which ensures message privacy and integrity. The PMIX SRS handles all X.509 certificate-based message encryption/decryption involved in communicating over the PMIX secure web service interface.

Installation Procedure

The steps listed below are intended to provide HCE technical staff with general guidance to which serves to augment the information contained in the PMIX SSP documentation. Please note that implementation may vary depending upon HCE's computer system. The IJIS Institute is available to provide technical assistance as needed.

Step 1: Download Package and Prepare the pre-installation checklist

- Download the following files from <http://builds.rxcheck.org/SRS/v3.2.1/final/hce/>
Windows: ***rxcheck-srs-hce-3.2.1-b<build number>.zip***
Linux: ***rxcheck-srs-hce-3.2.1-b<build number>-linux.zip***
- Download and Install latest JDK 21 from AdoptOpenJDK (Linux Only)
<https://adoptopenjdk.net/>

Add the following environment variables to the account .profile :

```
export JAVA_HOME=/opt/jdk-21.0.8+9
export PATH=$JAVA_HOME/bin
```

- Fill out and prepare the pre-installation checklist defined in Appendix A

Step 2: Network Preparation

- Configure and validate network connectivity between the State Routing Service and the two endpoint systems:
 - “External” - RxCheck Central Hub
 - “Internal” – HCE System
- The following steps, which are based on a typical configuration process, reflect general network configuration guidance and may need to be tailored to apply to specific environments.
 - **Network Access**
 - Enable the SRS to access the RxCheck Hub
 - Provide the PMIX RxCheck Administrator with the SRS external IP address so that they can configure the RxCheck Hub network firewall
 - Configure the networking components:
 - Add the necessary network address translation (NAT)
 - Add the routing rules needed to route outbound traffic
 - If necessary, add any outbound firewall rules
 - If the external IP address is “virtual”, ensure any added routing provisions are implemented

- **Domain Name Resolution**
 - RxCheck Hub
 - Identify the domain name and network address
 - Ensure the SRS can resolve the domain name to the IP


Step 3: Security

The following outline provides instructions (On Windows Server) to help acquire and install the X.509 certificate for the PMIX SRS:

- Generate SSL/TLS Custom CSR self-signed certificate (if necessary)
 - Open Microsoft Powershell Window (in Administrator mode)
 - Create the certificate using the following command that will be placed under the local machine and export the PFX and CER version of the certificate to be used in the installer

Create a Self-Signed Certificate

```
PS > New-SelfSignedCertificate -Subject "CN=_SITEID_" -KeyLength 2048 -NotBefore (Get-Date) -NotAfter (Get-Date).AddMonths(36) -CertStoreLocation "cert:\LocalMachine\My"
```



```
Administrator: Windows PowerShell
Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

Install the latest PowerShell for new features and improvements! https://aka.ms/PSWindows


PS C:\WINDOWS\system32> New-SelfSignedCertificate -Subject "CN=TT_HCE" -KeyLength 2048 -NotBefore (Get-Date) -NotAfter (Get-Date).AddMonths(36) -CertStoreLocation "cert:\LocalMachine\My"

PSParentPath: Microsoft.PowerShell.Security\Certificate:::LocalMachine\My
Thumbprint Subject
----- -----
B496FBC2ED13321DB0935F45B3EE6A0CB6824E14 CN=TT_HCE
```

Note: Copy the certificate Thumbprint to be used in the following steps.

Export the Private Key of the Certificate in PFX format

```
PS > $mypwd = ConvertTo-SecureString -String "password" -Force -AsPlainText
PS > Get-ChildItem -Path cert:\localMachine\my\[CERTIFICATE-THUMBPRINT] | Export-PfxCertificate -FilePath
e:\temp\_SITEID_.pfx -Password $mypwd
```



```
PS C:\WINDOWS\system32> $mypwd = ConvertTo-SecureString -String "Test@123" -Force -AsPlainText
PS C:\WINDOWS\system32> Get-ChildItem -Path cert:\localMachine\my\B496FBC2ED13321DB0935F45B3EE6A0CB6824E14 | Export-PfxCertificate -FilePath c:\RxCheck\temp\TT_HCE.pfx -Password $mypwd

Directory: C:\RxCheck\temp

Mode LastWriteTime Length Name
---- ----- ----- --
-a--- 3/27/2025 2:36 PM 2621 TT_HCE.pfx
```

Export the Public Key of the Certificate in DER format

```
PS > Get-ChildItem -Path cert:\localMachine\my\[CERTIFICATE-THUMBPRINT] | Export-Certificate -Type CERT -FilePath
"e:\temp\_SITEID_.cer"
```

```
PS C:\WINDOWS\system32> Get-ChildItem -Path cert:\localMachine\my\CF03367CEA87A8FE10F22605B455FFC4823E8E4A | Export-Certificate -Type CERT -FilePath "c:\RxCheck\temp\TT_HCE.cer"

Directory: C:\RxCheck\temp

Mode                LastWriteTime       Length Name
----                <-----           ----- 
-a----  3/27/2025  2:28 PM           768  TT_HCE.cer
```


Note: You can also create a self-signed certificate using OpenSSL tool.

Step 4: Install Application

Install RxCheck SRS Package

- Unzip **rxcheck-srs-hce-3.2.1-b<build number>.zip** file to a folder.

Windows:



Linux:

\$ unzip rxcheck-srs-hce-3.2.1-b<build number>-linux.zip

- Open command prompt and change directory to “bin” folder

Windows:

```
c:\> cd c:\rxcheck\rxcheck-srs-hce-3.2.1-b<build number>\bin
```

Linux:


```
$cd /home/rxcheck/rxcheck-srs-hce-3.2.1-b<build number>/bin
```

```
$chmod +x *.sh
```

- Install RxCheck SRS 3.2.1 as Windows Service by executing below command. (Windows Only)

Windows:

```
c:\rxcheck\rxcheck-srs-hce-3.2.1-b<build number>\bin>service.bat install  
"RxCheckSRS_3.1b<build number>"
```



Configure RxCheck SRS

- Change the folder to “conf” folder

Windows:

```
c:\> cd c:\rxcheck\rxcheck-srs-hce-3.2.1-b<build number>\conf
```

Linux:

```
$cd /home/rxcheck/rxcheck-srs-hce-3.2.1-b<build number>-linux/conf
```


- Rename *application.yml.template.XXX* file to *application.yml* file
- Edit *application.yml* using an editor like Notepad++ or VI and replace the variables with values listed in the table.

Variable Name	Description
APIKEY	API Key provided by RxCheck
SITEID	Site Id provided by RxCheck
_FULLPATH_KEYSTORE_FILE_	Full path to PFX certificate file containing the Private Key that was created in Step 3 of the installation.
KEYPASSWORD	Password for KeyEntry (entered in Step 3)

<u>_STOREPASSWORD_</u>	Password for the KeyStore (default is the same password as key password, entered in Step 3)
------------------------	---

Step 5: Complete SRS Configuration on the RxCheck Console

- Login to RxCheck Console using the credentials provided.




- Setup SRS Outbound Sender Endpoint Security

Set the username and password to secure the endpoints. Leave the fields blank if HTTP Basic Authentication is not required.


Field Name	Description	Default Value
Outbound Username	HTTP Basic Access Authentication Username	
Outbound Password	HTTP Basic Access Authentication Password	

- Upload SRS Public Key to RxCheck Console PKI database

- Enter Subject name used in Step 3 in the **Private Key Subject** field. Eg: TT_HCE




- Upload the public key. The certificate must be in DER encoded binary X.509 (.cer) format.




- Click “Save” button on the Site Configurations page.

Step 6: Starting RxCheck SRS

- Open Windows Services Manager. To open Windows Services, Run *services.msc* to open the Services Manager. Here you will be able to start, stop, disable, delay Windows Services. (Windows Only)



- Find Service “**RxCheckSRS_3.1b<build number>**” and change the Start Type to “**Automatic**” (Windows Only)



- Right click on the service name and “Start” the service. (Windows Only)
- Run the **startup.sh** from **bin** folder to start the SRS process (Linux Only)

- Open the following Service URLs in a browser to verify the services are running

PMIX2 Outbound SRS	http://localhost:8080/rxoutbound/service/pmix2?wsdl
-----------------------	---

Note: Replace localhost with the machine name or DNS name associated with the SRS server

Step 7: Conduct Simulator Testing

- Perform a simulator test in which a HCE sends a message to the simulator with state code “GG” and the simulator can respond back with a message.

Step 8: Integration Testing

- Perform integration testing with an exchange partner; the request will flow from the requesting-state PDMP application to the requesting-state SRS (Option 1) *or* the Custom Proxy (Option 2), to the RxCheck Hub, to the disclosing-state PDMP application (note: the response will follow the same steps in the reverse direction)

Appendix A: Pre-Installation Checklist

The following architecture diagram and pre-installation checklist table will orient the deployment team by identifying important system information prior to the software installation and configuration.




Figure 2: Typical RxCheck Integration Architecture Overview

ID	Description	Value
1.	SRS Outbound Host Base URL Address	http://____:8080/rxoutbound/service/pmix2
1.1	Domain Name:	
1.2	IP Address:	
2.	RxCheck Hub Service Host URL Address	https://uat.rxcheck.org:18803/RxCheck/hub
2.1	Domain Name:	uat.rxcheck.org
2.2	IP Address:	40.71.234.80

Table 1: Pre-Installation Checklist (UAT)

ID	Description	Value
1.	SRS Outbound Host Base URL Address	http://____:8080/rxoutbound/service/pmix2
1.1	Domain Name:	
1.2	IP Address:	
2.	RxCheck Hub Service Host URL Address	https://prod.rxcheck.org:18803/rxcheck/hub
2.1	Domain Name:	prod.rxcheck.org
2.2	IP Address:	52.227.138.130

Table 2: Pre-Installation Checklist (PROD)

Appendix B: Customizing SRS

1. Changing Server Ports

By default, the RxCheck SRS service runs on ports 8080 (http) and 8433 (https). If necessary, different ports can be configured in *server.xml* file located in *c:\rxcheck\ rxcheck-srs-hce-3.2.1-b<build number>\conf* folder.

- For HTTP port, modify the below XML element. Change the port 8080 to a desired port.

```
<Connector port="8080" protocol="HTTP/1.1" connectionTimeout="20000" redirectPort="8443" />
```

- For HTTPS port, modify the below XML elements. Change the port 8443 to a desired port.

```
<Connector port="8080" protocol="HTTP/1.1" connectionTimeout="20000" redirectPort="8443" />
```

```
<Connector SSLEnabled="true" clientAuth="false" keystoreFile="conf/keystore.jks" keystorePass="rxchecksrss" maxThreads="150" port="8443" protocol="HTTP/1.1" scheme="https" secure="true" sslProtocol="TLS"/>
```

```
<Connector port="8009" protocol="AJP/1.3" redirectPort="8443" />
```

2. Changing Server Certificate

A default self-signed certificate is included in the package for SSL/TLS transport layer. This must be replaced by either a new self-signed certificate or a certificate purchased from a CA in production environment.

- Creating a self-signed certificate.

```
C:\>keytool -genkey -keyalg RSA -alias selfsigned -keystore keystore.jks -storepass rxchecksrss -validity 720 -keysize 2048
```

- Copy the self-signed certificate keystore *keystore.jks* file to *c:\rxcheck\ rxcheck-srs-hce-3.2.1-b<build number>\conf* folder

3. Separate instances for Outbound and Inbound Services

If desired, separate instances of Outbound and Inbound SRS's can be installed on the same server or on a different sever by following the steps 1 through 6. This might be required due to the local network security requirements or for achieving higher performance throughput.

Based on the type of service you are installing, delete the other .war file from *c:\rxcheck\ rxcheck-srs-hce-3.2.1-b<build number>\webapps* folder.

4. Increasing JVM memory

By default, the Java process heap size is set for minimum 3072MB and maximum 6144MB. This must be changed to higher memory for production environment.

Memory parameters can be changed in setenv.bat (Windows) or setenv.sh (Linux) file located in the *bin* folder. You may need to uninstall and reinstall the service for changes to on windows server.


5. Uninstalling RxCheck SRS

To uninstall SRS process, execute command.

Windows:

```
c:\rxcheck\rxcheck-srs-hce-3.2.1-b<build number>\bin>service.bat uninstall "RxCheckSRS_3.1b<build number>"
```

Eg:



The screenshot shows a Windows Command Prompt window titled "Command Prompt". The command entered is "c:\rxcheck\apache-tomcat-8.5.32\bin>service.bat uninstall "RxCheckSRS_2.0"" and the output is:

```
c:\rxcheck\apache-tomcat-8.5.32\bin>service.bat uninstall "RxCheckSRS_2.0"
Removing the service '"RxCheckSRS_2.0"' ...
Using CATALINA_BASE: "c:\rxcheck\apache-tomcat-8.5.32"
The service '"RxCheckSRS_2.0"' has been removed

c:\rxcheck\apache-tomcat-8.5.32\bin>
```